Polycom® VSX™ 7000s

Features and Benefits



	Audio
Siren™ 14 Wideband Audio	 14 kHz crystal clear audio Eliminates fatigue associated with straining to hear every word CD-quality sound for dynamic audio performance Superb clarity to hear the subtleties of every word Included on every system
Polycom StereoSurround™	 2 channels of 14 kHz crystal clear audo Wideband audio projected in stereo, from left and right speakers Superb clarity to hear the subtleties of every word Easily decipher multiple, simultaneous conversations Distinguish which side of the room people are talking from, just like in a real meeting Enable easily in the user interface and by attaching speakers to the VSX 7000s
SoundStation VTX 1000® Integration	 Use the SoundStation VTX 1000 as the microphone for the video system and eliminate the VSX 7000s microphones Add audio calls to a video conference with the SoundStation VTX 1000 Maximize the value of audio and video equipment investments when used together Remarkable voice pickup range with the SoundStation VTX 1000 microphones Video dial, mute, call hangup and call redial from the SoundStation VTX 1000 keypad
Integrated Hi-Fidelity Sound System	 Eliminates reliance on TV speakers which deliver sub-par quality Includes mid-range speaker and subwoofer Rich, deep bass and broad audio range Small, compact form factor
Enhanced Microphone Array	 360° audio pickup Flotation feet filter out table-top noise Sensitive enough to pick up whispers, smart enough to eliminate unwanted background noise Versatile and attractive design for table top, wall or ceiling mount Single array for StereoSurround Gated enhanced stereo pickup
Audio Error Concealment	 Reduced audio drop-out on busy IP or ISDN networks Smooth, consistent verbal communications without interruptions Corrects audio from any system seamlessly Activates automatically, only when needed
	Video
H.264 Video up to 768Kbps	 Use less bandwidth to conduct video calls Unparalleled video quality for lower line rate applications More bandwidth is available for other business Cost savings to any organization
Pro-Motion™ H.263 Video	 Full-screen, TV-like video quality with fluid, precise motion handling Greater image detail with 50/60 fields per second Most natural video communications experience possible



Polycom VSX 7000s Features and Benefits

Single Monitor XGA Support	 Use a XGA display, or a TV for main display No need for a dual monitor system to clearly see content Flexibility in configuration, allowing users to use the display of their choice Supports up to 1024 x 768 resolutiob
Support for 16:9 or 4:3 Format	 User selectable display format 16:9 aspect ratio and Dual Monitor Emulation is perfect for plasma displays High resolution graphics displays for content presentation
Video Error Concealment	 Reduced video drop-out on busy IP networks Smooth, continuous video without interruptions Maintain active face-to-face contact Accomplish meeting objectives without worrying about the video integrity Activates automatically, only when needed
	Content Sharing
People+Content™, H.239	 Using Polycom's Visual Concert device, easily attach a laptop and display PC content during a video call The content source can come from a VCR/DVD or document camera Standards based H.239 ensures interoperability in the industry No matter what the content source, the conference participants will always see the content and the speaker simultaneously
People+Content IP	 Users can share data during a video conference without having to connect their PC to the system. Simply input the IP address into a small utility and PC content is automatically shown to all conference participants This feature can be used by anyone in the conference, even audio callers! An excellent option for wireless laptop users who are participating in a video conference
Adjustable Bandwidth for Content	 Choose the amount of bandwidth to dedicate to Content and People Options include 90% Content/ 10% People; 50% Content/ 50% People; 10% Content/ 90% People Adjustable setting located on the on-sreen interface that can be accessed both during a call and outside of a call
Dedicated VCR/DVD Connection	 Ability to use line level inputs for other devices Easily play VCR/DVD movies/images during a video conference Adds another dimension to the conference, making it like "being there" See both the speaker and the DVD/VCR image
	User Interface
Calendar & Call Scheduler	 Quick and easy access to a monthly calendar with current date and time posting Schedule repeat meetings to dial automatically Create and save multipoint team meetings
Customizable Home Page	 Display only the necessary buttons Unique design to meet your organization's needs Simplified graphical interface for novice users Easy to understand icon driven menu navigation decreases learning curve Leads to increased use of video
Dual Monitor Emulation	 Use Dual Monitor Emulation for the most efficient use of a single display Dual monitor capability allows users to connect a TV as the main display and a VGA as the second display for content Full size near and far video windows at the same time Alternate layout views
User Selectable Camera Icons	 Use icons that represent your industry Intuitive icons match the input device Custom name gives the icon clear meaning Selection – 5 libraries to choose from Decreases learning curve

Polycom VSX 7000s Features and Benefits

Interoperability		
Part of The Polycom Office™	 Remote management through Global Management System™ 	
	 Click & View™ offers a variety of layout templates for a multi-point call 	
	 Expand the audience over audio and video with an MGC™ bridge 	
	 Extended conferencing with Polycom PathNavigator™ 	
	 Schedule, invite participants and manage conferences easily with Polycom Conference Suite 	
	 Expand meeting capbilities by adding voice-only participants using the SoundStation VTX 1000 conference phone 	
Standards-based	Solid, reliable platform	
	 Qualified by independent test labs 	
	 Interoperates with other vendor's systems 	
	Easy to install even in a multi-vendor environment	
Baseline Mode	 Set your system to baseline mode, H.261 and G.711, for maximum interoperability with legacy video conferencing systems 	
	 Accessible via the web interface for easy access by the network administrator 	
	Can be turned on and off as needed	

© 2005 Polycom, Inc. All rights reserved.

Polycom, the Polycom logo design, ViewStation, SoundStation VTX 1000 and ViaVideo are registered trademarks and VSX, Pro-Motion, People+Content, iPower, MGC,PPolycom athNavigator, Global Management System, Click & View, StereoSurround, VIU and The Polycom Office are trademarks of Polycom, Inc. in the U.S. and various countries.

Polycom, Inc. in the U.S. and various countries.

All other trademarks are the property of their respective companies. Specifications are subject to change without notice.



Polycom Headquarters:

4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only. For North America, Latin America and Caribbean (T) +1.925.924.6000, (F) +1.925.924.6100

Polycom EMEA: 270 Bath Road, Slough, Berkshire SL1 4DX, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010

Polycom Asia Pacific: Polycom Hong Kong Ltd., Rm 1101 MassMutual Tower, 38 Gloucester Road, Wanchai, Hong Kong, (T) +852.2861.3113, (F)+852.2866.8028